


RT D1295DD 3D media player Product Specifications

Model : R9 PLUS

Main Points	
<ol style="list-style-type: none"> 1. Realtek 1295 chipset, ARM CA53 x4,Mali-T820 MP3 L2 Cache 1MB. 2G DDR4, 16G EMMC; 2. Powered by Android6.0.1; 3. Support H.265 4K@60fps; 4. HDMI in + HDMI2.0 out; 5. LAN : 10/100M/1000M Ethernet; 6. SATA3.0: internal 3.5"SATA HDD; 7. Can play original BD disk,BD ISO playback; 8. Support Frame Packaging 3D, 2D movie convert to 3D image; 9. Support VP9,4KP60 for Youtube 4K; 10. Support 802.11 Ac a/b/g/n,2.4G/5.8 Dual Band WIFI. Support PVR function; 11. KODI17.0 Pre-installed Fully Loaded; 12. Bluetooth V4.0; 13. Miracast and Intel Wireless Display; 14. Support 7.1 pass through, Support Dolby True HD,DTS-HD MA,LPCM,Dolby Digital Plus. 	
Hardware	
CPU	RTD1295 DD ,ARM CA53X4, Mali-T820 MP3 L2 Cache 1MB
RAM	2GB DDR4
Storage	16GB EMMC
Interface	
Video Output	HDMI2.0
Wireless	802.11 a/b/g/n,2.4G/5.8 Dual Band WIFI
LAN	10/100M/1000 Ethernet
WLAN(Router)	802.11ac
Composite Audio /Video	AV output
Optical	Optical output
Coaxial	Coaxial output
HDMI INPUT	HDMI2.0 input with PVR function
HDMI output	HDMI2.0 output
USB 3.0	USB 3.0 host
USB2.0	USB 2.0 host x 3
TYPE-C	TYPE-C HOST and Slave
SATA3.0	Internal 3.5"SATA
SD/MMC card reader	3.0
Power	12V 2.5A power adaptor
Android system	

Android Version	Android 6.0.1
File System	Fat16 / Fat32 / exFAT/NTFS/HFS+/Samba/ext2/3/4
Menu Language	English/German/Spanish/France/Italia/Nederland/Poland/Russia/Korean/Japanese/Simplified Chinese/Chinese-traditional
System Upgrade	OTA upgrade or USB upgrade
Video Streaming	HTTP、RTSP
Media	
Video Container	<ul style="list-style-type: none"> ➤ RM/RMVB ➤ MPEG1/2/4 Elementary (M1V, M2V, M4V) ➤ MPEG1/2 PS (M2P, MPG) ➤ MPEG2 Transport Stream (TS, TP, TRP, M2T, M2TS, MTS) ➤ VOB ➤ AVI, ASF, WMV ➤ Matroska (MKV) ➤ MOV (H.264), MP4, RMP4 ➤ IFO ➤ DVD-ISO,BD-ISO ➤ MINI BD,BD-9,BD25 , RBD , D5 , D9 , DVD , CD ➤ FLV ➤ swf/(.swf) * ➤ 3GP/.3gp ➤ AVS/(.avs) ➤ 3D Bluray(DISC/ISO) or Single-File(*.ts/*.m2ts)
Video Decode	<ul style="list-style-type: none"> ➤ 4KP60 10bit/HDR/HDMI 2.0 Tx& Rx/H264 encoder ➤ VP9 4KP60 ➤ H.265 /HEVC 4K*2K(MP@L5.0 High Tier) ➤ MPEG1,VCD1.0/2.0,SVCD(up to1920*1080@30P/60I or 1280*720@60P) ➤ HD MPEG2 MP/HL, ISO, IFO, VOB, TS(up to1920*1080@30P/60I or 1280*720@60P) ➤ HD MPEG4 SP/ASP, Xvid(up to1920*1080@30P/60I or 1280*720@60P) ➤ H.263(Profile0/3@L70 1080@60P) ➤ H.264 BP,MP,HP@L4.2, H.264 MVC SHP (maximum 720@30P) ➤ WMV9,VC-1 AP@L3(up to 1920*1080@30P/60I or 1280*720@60P) ➤ DivX3/4/5(up to1920*1080@30P/60I or 1280*720@60P) ➤ XVID SD/HD(up to 1920*1080@30P/60I or 1280*720@60P) ➤ RM/RMVB 8/9/10(up to 1280*720@30P) ➤ AVS: Jizhum profile @ level 2.0/ 4.0/ 4.2/ 6.0/ 6.2
Audio Container	<ul style="list-style-type: none"> ➤ aac,mp4,m4a ➤ MPEG audio (mp1, mp2, mp3, mpa) ➤ wav ➤ wma,asf ➤ ogg ➤ ape ➤ flac ➤ amr,3ga ➤ ra, rm, rmvb,ram

Audio Decode	<ul style="list-style-type: none"> ➢ MPEG I Layer 1/2/3(2-CH) and MPEG 1/2(Multi -Channel) ➢ LPCM,ADPCM,FLAC,AAC,ALAC,AMR,WAV,WMA,WMA pro,OGG,AMR,APE ➢ DTS digital+stereo ➢ Dolby Digital AC3 ➢ Dolby Digital Plus ➢ Dolby Digital TrueHD ➢ RA-cook/RA-Lossless
Picture Formats	JPEG ,BMP, PNG, GIF, TIFF, Webp(Android)
Subtitle formats	<ul style="list-style-type: none"> ➢ MicroDVD [.sub], ➢ SubRip [.srt], ➢ Sub Station Alpha [.ssa], ➢ Sami [.smi] ➢ VobSub[.idx+.sub] ➢ Advance SubStation Alpha[.ass]
Subtitle Language	➢ Standard version: simplified Chinese, traditional Chinese, Turkish, Greek, Hebrew, Czech, SE European, Central European, Cyrillic, Western, UTF8, etc
Menu Language	➢ Standard version: simplified Chinese, traditional Chinese, English, Russian, Spanish, Czech, Dutch, Italian, French, German, Turkish, Hebrew, etc
HDD format	➢ Support FAT32, NTFS, EXT3, EXT4,HFS
Case	
Material & Craft	Aluminum case
Color	Black
Unit Dimension	200*143*55MM
Unit Weight	1.8kg
Accessories	
IR remote control	x1pcs (Optional: 2.4G air mouse)
HDMI cable	x1pcs
Power adaptor	x1pcs
Warranty Card	x1pcs
Quick Install Guide	x1pcs
Others	
Certification	RoHS、 CE、 FCC
Operating Temperature	0~70°C
Storage Humidity	30%~70%
Storage Temperature	10~35°C
Overall Power Consumption	<5W
Standby Power Consumption	<0.02W
QTY/CTN	6PCS